

Programmable Operator Interface

MONITOUCH



Refined black body

V9

Black Model

Specifications

Standard

Model	Display size	Resolution	Touch switch	Video/RGB ^{*1}	AUDIO output	Wireless LAN	Extended wired LAN	UL508	CE	KC	Power supply
V9120iSB	12.1"	800×600	Analog resistive film	✓	✓						AC
V9120iSBD	12.1"	800×600	Analog resistive film	✓	✓			✓	✓		DC
V9120iSLBD	12.1"	800×600	Analog resistive film	✓	✓		✓	✓	✓		DC
V9100iSB	10.4"	800×600	Analog resistive film	✓	✓						AC
V9100iSBD	10.4"	800×600	Analog resistive film	✓	✓			✓	✓		DC
V9100iSLBD	10.4"	800×600	Analog resistive film	✓	✓		✓	✓	✓		DC
V9080iSBD	8.4"	800×600	Analog resistive film	✓	✓			✓	✓		DC
V9080iSLBD	8.4"	800×600	Analog resistive film	✓	✓		✓	✓	✓		DC

*1 Optional unit GUR-XX is necessary.

Lite

Model	Display size	Resolution	Touch switch	Video/RGB	AUDIO output	Wireless LAN	Extended wired LAN	UL508	CE	KC	Power supply
V9100iCB	10.4"	640×480	Analog resistive film								AC
V9100iCBD	10.4"	640×480	Analog resistive film					✓	✓		DC
V9080iCBD	8.4"	640×480	Analog resistive film					✓	✓		DC
V9060iTBD	5.7"	640×480	Analog resistive film					✓	✓		DC

Type

V9 0i B

① ② ③ ④

- ① Display size (12/10/08/06)
- ② Device type (S/T/C)
- ③ Extended wired LAN I/F (L/None)
- ④ Power supply (D/None)

Case color

B Black (front case and surface sheet)*2

*2 The rear case is standard color (light gray).

Line-up

Standard



12.1" SVGA (800×600)

V9120iSB
V9120iSBD
V9120iSLBD
V9120iSRBD



10.4" SVGA (800×600)

V9100iSB
V9100iSBD
V9100iSLBD
V9100iSRBD



8.4" SVGA (800×600)


V9080iSBD
V9080iSLBD
V9080iSRBD

Lite



10.4" VGA (640×480)

V9100iCB
V9100iCBD



8.4" VGA (640×480)

V9080iCBD



5.7" VGA (640×480)

V9060iTBD

Hakko Electronics Co., Ltd. www.monitouch.com

[Overseas Sales Department]
890-1 Kamikashiwano-machi, Hakusan, Ishikawa 924-0035, Japan
TEL. +81-76-274-2144 E-mail : sales@hakko-elec.co.jp